

KYOCERA KCL6448HSTT-X14

PANEL CHARACTERISTICS

Unit : STN-LCD DD 16 BITS
 Display format : 640 X 480
 Colors : 8 (passive matrix)

TEK932 BIOS & JUMPER INFORMATION

BIOS : VAE_AHB
 Jumper: W10: Short 1-2

TECHNICAL INFORMATION

Display Flat Panel and CRT simultaneously.

Note 1: Use ENVEE signal with an external control circuit to switch the VLCD power VEE on the Flat Panel.

DISPLAY INTERCONNECTION (or use a dapter - see before)				
TEK932		EXTERNAL	FLAT PANEL	
Signal Name	PIN #		PIN #	Signal Name
ENAVDD	1			
Vcc (+5V)	2		24	VDD
			26	BS
ENVEE	3	See Note 1	3	DISP.OFF
			27-28	VEE
STNDBYE*	4			
ENABLK	5			
M/DE	7		2	DF
ACTI	8			
LP/DE	10		4	LOAD
FLM	11		1	FRM
SHFCLK	13		6	CP
P0	15		15	HD7
P1	16		14	HD6
P2	18		13	HD5
P3	19		12	HD4
P4	21		23	LD7
P5	22		22	LD6
P6	24		21	LD5
P7	25		20	LD4
P8	27		11	HD3
P9	28		10	HD2
P10	30		9	HD1
P11	31		8	HD0
P12	33		19	LD3
P13	34		18	LD2
P14	36		17	LD1
P15	37		16	LD0
P16	39			
P17	40			
P18	42			
P19	43			
P20	45			
P21	46			
P22	48			
P23	49			
		N.C.		
POWER LCD		VLCD		
		Vadj	29	VCONT
GND	6-9-12-14-17-20-23-26-29-32-35-38-41-44-47-50		5-7-25	VSS

TEKNOR

INDUSTRIAL COMPUTERS INC.